C-634 HEAVY



COMMERCIA



The PRIER C-634 heavy commercial wall hydrant is key operated, code approved, and flows up to 16 GPM at 25 PSI differential. This commercial hydrant is self-draining even with a closed end hose attached.













- Field testable as required by ASSE 1052, pressure rated to 125 PSI, temperature to 140°
- Heavy pattern cast brass hydrant for use with or without brass or aluminum box
- Patented PRIER "triple seal" positive shutoff system offers triple redundancy to assure shutoff
- Tested to 250,000 cycles; designed to last the life of the plumbing system
- Heavy duty brass piping, significantly stronger than copper, with threaded and sealed joints
- Every hydrant comes with a wall clamping ring for more secure installation
- Gasket is included with every box and prevents water and air intrusion into the building
- Four box options including satin nickel plated(BX1), rough brass(BX2) or aluminum(BX3)
- Satin nickel plated round box (RB1) installs through 6" hole or 6" Schedule 40 PVC sleeve





C-633 MILD





CLIMATE

COMMERCIAL

HYDRANT

The PRIER C-633 comes in two models close coupled (CC) and swivel (SV). These commercial hydrants are self-draining even with a closed end hose attached.













- Listed and labeled to ASSE 1019-B and ASSE 1052, IAPMO/C-UPC
- · Patented PRIER "Triple Seal" positive shutoff system offers triple redundancy to assure shutoff
- Self-draining, even with hose attached and under pressure
- Tested to 250,000 cycles; designed to last the life of the plumbing system
- C-633NSV inlet can be rotated 360° to simplify installation
- Four box options including satin nickel plated(BX1), rough brass(BX2) or aluminum(BX3)
- Satin nickel plated round box (RB1) installs through 6" hole or 6" Schedule 40 PVC sleeve
- Gasket is included with every box and prevents water and air intrusion into the building

